



Product Information

PSF-5cSt Silicone Bath Fluid

Operating Temperature Range: -70°C to 65°C (open system) / -70°C to 150°C (closed system)



Pure Silicone Fluid 5cSt Silicone Bath Fluid is a low viscosity 100% silicone that has a service temperature range of -70°C to 150°C closed system.

PSF-5cSt Silicone Bath Fluid is a clear, colorless and odorless low-viscosity Linear Polydimethylsiloxane (CAS # 63148-62-9) that is formulated for use as a low temperature baths fluid and a low temperature heat transfer fluid.

In **open system** baths, **PSF-5cSt Silicone Bath Fluid** has an **operating temperature range of -70°C to 65°C**. In **closed system***, the operating temperature range is wider due to the absence of air. The **closed operating range is -70°C to 150°C**.

PSF-5cSt Silicone Bath Fluid has a low viscosity-temperature coefficient or V.T.C. (viscosity @99°C ÷ viscosity @ 38°C). Thus, it will not exhibit a wide viscosity increase at the lower temperatures. For example, at -40°C, its viscosity increases to only 40cSt. This is critical for baths that have pumping systems that cannot operate with higher viscosity fluids.

Bath Applications include: low temperature open system baths, low temperature closed system baths, constant temperature baths, circulating baths, low temperature refrigerated baths, refrigerated circulators, recirculating coolers, cold temp calibration baths, closed loop baths, heat transfer baths, heat transfer fluid in freeze drying equipment, thermostats and cryostats

*Closed system baths are systems from which air has been excluded

Specifications

Product Code	PSF-5cSt
Chemical Name	Polydimethylsiloxane
CAS #	63148-62-9
Appearance	Clear, colorless, odorless fluid
Viscosity Class	Low
Non-Flammable	Yes
Thermally Stable	Yes
Availability	1 - 5 - 55 gallon containers
Minimum Order	1-gallon (3.785 liters)

Features

- 100% silicone fluid
- Low viscosity: 5cSt @ 25°C
- Excellent Low Temp Serviceability
- Hydrophobic – insoluble with water
- Compatible with virtually all o-rings, gaskets, hoses, valves and seals*
- Chemically Inert
- Low Viscosity-temp-coefficient (V.T.C)... 0.54
- Low Vapor pressure
- Low Service temperature range of -70°C
- Low Pour Point: -90°C
- Flash Point: 135°C
- High Resistance to Oxidation
- VOC Exempt

*Not recommended for silicone o-rings....may cause swelling.

Viscosity @ temperature

Viscosity-Temperature-coefficient...0.54
Viscosity @ 25°C.....5cSt (centistokes)
Viscosity @ 0°C.....8cSt
Viscosity @ -20°C.....14cSt
Viscosity @ -40°C.....40cSt

Packaging:

1-gallon.....	3.45kg
5-gallon pail.....	17.25kg
4 x 5-gallon pails	
55-gallon drum.....	190kg
F.O.B. Phila, PA U.S.A.	

Typical Product Data

Specific Gravity	Viscosity-Temp Coefficient	Flash Point	Pour Point	Refractive Index	Thermal Expansion cc/cc °C	Thermal Conductivity @ 25C g/cal/cm/sec °C	Surface Tension	Dielectric Constant	Dielectric Strength volts/mil
0.918	0.54	135°C	-90°C	1.3970	0.00109	0.00028	19.7	2.60	375

Typical Product Data (cont'd)

Boiling Point	Vapor Density (air = 1)	Vapor Pressure @ 25°C	Max volatility, % wt loss @ 150°C	Molecular weight
>200°C	>1	1mmHg	90	770

For More Information, Contact:

Clearco Products Co., Inc.

3430 G. Progress Drive

Bensalem, PA 19020

Tel: 215 639-2640

Fax: 215 639-2919

Email: info@clearcoproducts.com

Web: www.clearcoproducts.com