



Pure Silicone Fluid 10,000cSt

High Viscosity Polydimethylsiloxane Fluid (CAS # 63148-62-9)...meets VV-D-1078 Silicone as Damping Fluid



PSF-10,000cSt Silicone Damping Fluid is a high viscosity polydimethylsiloxane that meets federal spec VV-D-1078 "Silicone as Damping Fluid".

PSF-10,000cSt Silicone Damping Fluid is a high viscosity linear Polydimethylsiloxane (CAS#63148-62-9) fluids with a viscosity of 10,000cSt (centistokes) @ 25°C.

PSF-10,000cSt Silicone Damping Fluid is a hydrophobic fluid that is characterized by its wide service temperature range, high oxidation resistance, high viscosity, high dielectric strength, high resistance to shear, low pour points, low V.T.C. (little viscosity change even at extremely low temperature), excellent lubrication & high damping action.

PSF-10,000cSt Silicone Damping Fluid meets Federal Spec VV-D-1078 "Silicone as Damping Fluid". It is used in a wide range of military and industrial liquid filled gauges, level controllers, rotary dampers, temperature and process recorders, control valves, calibration equipment, flow meters, thermostats, dashpots, monitoring systems avionic gauges and aviation instruments to dampen vibration, dampen pulsation, and dampen torque.

PSF-10,000cSt Silicone Damping Fluid is particularly effective for use in instruments and gauges that will operate at a wide service temperature range. The fluid is hydrophobic and prevents humidity from entering the gauge/instrument housing. This is very important. At low temperatures, water condensation can freeze and cause damage to the sensitive parts within the gauge/instrument housing. Ultimately, **Silicone Damping Fluids** will extend the service life of the equipment that it fills and provide more accurate readings even in the harshest of conditions.

Specifications

Chemical Name	Polydimethylsiloxane
Federal Spec	VV-D-1078
NSN No	NSN 9150-00-024-9621 (50cSt >)
CAS #	63148-62-9
Appearance	Clear, colorless odorless fluid
Consistency	Honey

Properties

Appearance	Clear
Specific Gravity	0.975
Refractive Index	1.4035
Flash Point (Open Cup) °C	315°C
Pour Point °C	-48°C
V.T.C.	0.61
Surface Tension @ 25°C	21.5
Thermal Conductivity g/cal/cm/sec °C	0.00038
Thermal Expansion cc/cc °C	0.00096
Dielectric Constant 50Hz	2.75
Dielectric Strength (volts/mil)	400

Features

- Dampen vibration in gauges, instruments, meters and avionic instruments
- Protects internal components against vibration, freezing and corrosion.
- Extends service life of gauges, instruments, meters and avionic instruments.
- Wide Service Temperature Range
- High Oxidation resistance
- Low viscosity change at temperature (low V.T.C.)
- Inert to virtually all o-rings, gaskets, seals and valves *
- High Dielectric Strength
- Meets NSN 9150-00-024-9621 (50cSt >)
- Meets VV-D-1078 "Silicone as Damping Fluid"

* not recommended for Silicone o-rings due to possibility of swelling

Packaging

1-gallon pail.....	8lb / 3.6kg
5-gallon pail.....	40lb / 18kg
4 x 5-gallon pails	
55-gallon drum.....	190kg to 200kg
Terms F.O.B. Phila., PA U.S.A.	

Environmental & VOC Status

Clearco Pure Silicone Fluid is exempt from Federal VOC Regulations, including California (CARB) and OTC Regulations. It does not contribute to ozone depletion and global warming. In addition, it meets the following:

- RoHS Compliant
- HAP-free
- VOC Exempt

For More Information, Contact:

Clearco Products Co., Inc.
 3430 G. Progress Drive
 Bensalem, PA 19020
 Tel: 215 639-2640
 Fax: 215 639-2919
 Email: info@clearcoproducts.com
 Web: www.clearcoproducts.com