



PSF-2cSt Silicone Damping Fluid

Meets VV-D-1078 "Silicone as Damping Fluid"



PSF-2cSt meets VV-D-1078 Silicone as Damping Fluid.

PSF-2cSt Damping Fluid is a super-low viscosity linear Polydimethylsiloxane composed mainly of Dodecamethylpentasiloxane (CAS#141-63-8). The fluid is clear, colorless and essentially odorless with a viscosity of 2cSt (centistokes) @ 25°C.

PSF-2cSt Damping Fluid is a hydrophobic fluid that is characterized by its low viscosity, low pour point (-100°C), low V.T.C. (little viscosity change even at extremely low temperature), low surface tension (high spreadability), excellent lubrication, high damping action

PSF-2cSt Damping Fluid meets Federal Spec **VV-D-1078 "Silicone as Damping Fluid and exhibits Newtonian behavior under shear.** It is used in a wide range of military and industrial liquid filled gauges, level controllers, rotary dampers, temperature and process recorders, control valves, calibration equipment, flow meters, thermostats, dashpots, monitoring systems avionic gauges and aviation instruments to dampen vibration, dampen pulsation, and dampen torque.

PSF-2cSt Damping Fluid is particularly effective for use in instruments and gauges that will operate at extremely low temperatures (pour points is -100°C). It is hydrophobic and prevents humidity from entering the gauge/instrument housing. This is very important. At low temperatures, water condensation can freeze and cause damage to the sensitive parts within the gauge/instrument housing. Ultimately, **Silicone Damping Fluids** will extend the service life of the equipment that it fills and provide more accurate readings even in the harshest of conditions.

Specifications

Product code	PSF-2cSt
Chemical family	Polydimethylsiloxane
Chemical name	Dodecamethylpentasiloxane
CAS No.	CAS# 141-63-8
Appearance	Clear, colorless, odorless fluid
Meets NSN	NSN 9150-00-754-2600
Federal Spec	VV-D-1078 Silicone as damping fluid
Minimum Order	1-gallon

Features

- Dampen vibration in gauges, instruments, meters and avionic instruments
- Protects internal components against vibration, freezing and corrosion.
- Extends service life of gauges, instruments, meters and avionic instruments.
- Excellent low service temperature range
- Low viscosity change at temperature (low V.T.C.)
- Inert to virtually all o-rings, gaskets, seals and valves *
- Meets NSN 9150-00-754-2600
- High Dielectric Strength

* not recommended for Silicone o-rings due to possibility of swelling

Typical Product Data

Viscosity	Specific Gravity	Viscosity-Temp Coefficient	Flash Point	Pour Point	Refractive Index	Thermal Expansion cc/cc °C	Thermal Conductivity g/cal/cm/sec °C	Surface Tension	Dielectric Constant	Dielectric Strength volts/mil
2cSt	0.873	0.48	75°C	-100°C	1.3900	0.00117	0.00026	18.7	2.45	350

Product Data (cont'd)

Boiling Point	Vapor Density (air = 1)	Vapor Pressure @ 25°C	Evaporation rate Butyl acetate = 1	Molecular weight
229°C	>1	1mmHg	<1	410

Packaging

1-gallon.....	3.28kg
5-gallon pail.....	16.4kg
55-gallon drum.....	170kg
F.O.B. Phila, PA U.S.A.	

For More Info, Contact: Clearco Products Co., Inc.

15 York Road
Willow Grove, PA 19090
U.S.A.

Tel: (215) 366-7860

Fax: (215) 366-7862

Email: info@clearcoproducts.com

Web: www.clearcoproducts.com