



PSF-5cSt Silicone Damping Fluid

Meets VV-D-1078 "Silicone as Damping Fluid"



Pure Silicone Fluid 5cSt meets VV-D-1078 Silicone as Damping Fluid.

PSF-5cSt Damping Fluid is a low viscosity linear Polydimethylsiloxane (CAS#63148-62-9) fluid with a viscosity of 5cSt (centistokes) @ 25°C.

PSF-5cSt Damping Fluid is a hydrophobic fluid that is characterized by its low viscosity, low pour point (-90°C), low V.T.C. (little viscosity change even at extremely low temperature), low surface tension (high spreadability), excellent lubrication & high damping action

PSF-5cSt Damping Fluid meets Federal Spec VV-D-1078 "Silicone as Damping Fluid and exhibits Newtonian behavior under shear". It is used in a wide range of military and industrial liquid filled gauges, level controllers, rotary dampers, temperature and process recorders, control valves, calibration equipment, flow meters, thermostats, dashpots, monitoring systems avionic gauges and aviation instruments to dampen vibration, dampen pulsation, and dampen torque.

PSF-5cSt Damping Fluid is particularly effective for use in instruments and gauges that will operate at extremely low temperatures (pour points is -90°C). The fluid is hydrophobic and prevents humidity from entering the gauge/instrument housing. This is very important. At low temperatures, water condensation can freeze and cause damage to the sensitive parts within the gauge/instrument housing. Ultimately, **Silicone Damping Fluids** will extend the service life of the equipment that it fills and provide more accurate readings even in the harshest of conditions.

Specifications

Chemical Name	Polydimethylsiloxane
INCI/CTFA Name	Dimethicone
CAS #	63148-62-9
Appearance	Clear Liquid – Odorless & Tasteless
Viscosity Class	Low
Non-Flammable	Yes
Thermally Stable	Yes
Availability	1 – 5 – 55 gallon drums
NSN No's	NSN 9150-00-435-2712 NSN 9150-00-087-4046 NSN 9150-00-137-6343
Minimum Order	1-gallon

Features

- Dampen vibration in gauges, instruments, meters and avionic instruments
- Protects internal components against vibration, freezing and corrosion.
- Extends service life of gauges, instruments, meters and avionic instruments.
- Excellent low service temperature range
- Low viscosity change at temperature (low V.T.C.)
- Inert to virtually all o-rings, gaskets, seals and valves *
- Meets NSN 9150-00-435-2712
- Meets NSN 9150-00-087-4046
- Meets NSN 9150-00-137-6343
- High Dielectric Strength

* not recommended for Silicone o-rings due to possibility of swelling

Typical Product Data

Specific Gravity	Viscosity-Temp Coefficient	Flash Point	Pour Point	Refractive Index	Thermal Expansion cc/cc/°C 0-150°C	Thermal Conductivity @ 25C g/cal/cm/sec °C	Surface Tension	Dielectric Constant	Dielectric Strength
0.918	0.54	135°C	-90°C	1.3970	0.00109	0.00028	19.7	2.60	375

Product Data (cont'd)

Boiling Point	Vapor Density (air = 1)	Vapor Pressure @ 25°C	Max volatility, % wt loss @ 150°C	Molecular weight
>200°C	>1	<10mmHg	90%	770

Packaging:

1-gallon pail.....	3.45kg
5-gallon pail.....	17.25kg
4 x 5-gallon pails	
55-gallon drum.....	190kg

F.O.B. Phila, PA

For More Information, Contact:

Clearco Products Co., Inc.
3430 G. Progress Drive
Bensalem, PA 19020
Tel: 215 639-2640
Fax: 215 639-2919
Email: info@clearcoproducts.com
Web: www.clearcoproducts.com