



## PSF-20cSt Silicone Heat Transfer Fluid

**Operating Temperature Range: -50°C to 220°C (closed system)**



PSF-20cSt Heat Transfer Fluid offers a wide service temperature range.

**PSF-20cSt Silicone Heat Transfer Fluid** is a clear, colorless and odorless low-viscosity linear Polydimethylsiloxane (CAS No. 63148-62-9) that is formulated as a cold and heat transfer medium in a wide range of applications. **PSF-10cSt Low Temperature Silicone Bath Fluid** has an operating service temperature range of -50°C to 220°C (closed system\*).

**PSF-20cSt Silicone Heat Transfer Fluid** is characterized by its low pour points, low temperature stability, wide service temperature range, low viscosity change at temperature (low V.T.C.), low surface tension, long service life, and hydrophobic nature (insoluble in water).

**PSF-20cSt Silicone Heat Transfer Fluid** has a Thermal Conductivity value of 0.00034 g/cal/cm/sec °C. Its specific heat value is 1.6 (J/g °C)

**PSF-20cSt Silicone Bath Fluid** has a low viscosity-temperature coefficient or V.T.C. (viscosity @99°C ÷viscosity @ 38°C). Thus, its viscosity will not significantly increase even at extremely low temperatures. For example, at -40°C, its viscosity increases to only 125cSt. This is critical for baths that have pumping systems that cannot operate with higher viscosity fluids.

Applications include: low temperature heat transfer systems, heat transfer baths, heat transfer fluid in freeze drying equipment, calibration bath fluids for low temperature, low temperature closed system baths, low temperature constant temperature baths, low temperature circulating baths, low temperature circulator baths, low temperature refrigerated baths, low temperature closed loop baths,

\*Closed system baths are systems from which air has been excluded

### Specifications

Product Code	PSF-20cSt
Chemical Name	Polydimethylsiloxane
CAS #	63148-62-9
Appearance	Clear, colorless liquid
Viscosity Class	Low
Non-Flammable	Yes
Thermally Stable	Yes

### Features

- 100% silicone fluid
- Non-Flammable
- Excellent Low & Medium Temp Serviceability
- Hydrophobic – insoluble with water
- Compatible with virtually all o-rings, gaskets, hoses, valves and seals\*
- Chemically Inert
- Low Service Temperature Range
- Clear, Colorless, Odorless
- Low V.T.C...viscosity remains low even at very low temps
- Low Vapor pressure
- Low Pour Point: -65°C
- Flash Point: 232°C
- High Resistance to Oxidation

\*Not recommended for silicone o-rings...may cause swelling.

### Viscosity @ temperature

Viscosity-Temperature-coefficient...	0.59
Viscosity @ 25°C.....	20cSt (centistokes)
Viscosity @ 0°C.....	35cSt
Viscosity @ -20°C.....	60cSt
Viscosity @ -40°C.....	125cSt

### Typical Product Data

Specific Gravity	Refractive Index	Pour Point	Flash Point	Surface Tension	Thermal Conductivity @ 25°C g/cal/cm/sec °C	Thermal Expansion cc/cc °C	Specific Heat @ 25°C J/g °C
0.950	1.4000	-65°C	232°C	20.6	0.00034	0.00107	1.6

### Typical Product Data (cont'd)

Volume Resistivity	Molecular weight	Dielectric constant 50Hz	Dielectric strength volts/mil
≥1	2,000	2.72	375

### Packaging

1-gallon.....	3.6kg
5-gallon pail.....	18kg
55-gallon drum.....	190kg
Terms F.O.B. Phila, PA	

### For More Information, Contact:

#### Clearco Products Co., Inc.

3430 G. Progress Drive

Bensalem, PA 19020

Tel: 215 639-2640

Fax: 215 639-2919

Email: [info@clearcoproducts.com](mailto:info@clearcoproducts.com)

Web: [www.clearcoproducts.com](http://www.clearcoproducts.com)