

CLEARCO PRODUCTS

3430 G Progress Drive, Bensalem, PA 19020

Phone: (215) 639-2640

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **POLYDIMETHYLSILOXANE – PSF-1.5cSt**

CHEMICAL NAME: POLYDIMETHYLSILOXANE

SYNONYMS: OCTAMETHYLTRISILOXANE; MDM

CHEMICAL FAMILY: SILICONE

HMIS CODES HEALTH: 1 FLAMMABILITY: 3 REACTIVITY: 0

INGREDIENTS

IDENTITY	CAS NO.	%	TLV OSHA PEL
HEXAMETHYLDISILOXANE	107-46-0	<2	not established
OCTAMETHYLTRISILOXANE	107-51-7	3-75	not established
DECAMETHYLTETRASILOXANE	141-62-8	3-95	not established
DODECAMETHYLPENTASILOXANE	141-63-9	3-95	not established
TETRADECAMETHYHEXASILOXANE	107-52-8	3-75	not established
HIGHER LINEAR SILOXANES	63142-62-9	<5	not established

PHYSICAL DATA

Boiling Point: >150°C

Specific Gravity: 0.85

Vapor Density (air = 1): >1

% volatiles: 100

Molecular Weight: 237-550

Appearance & Color: Clear, nearly odorless liquid

Freezing Point: (-86°C)

Vapor Pressure, 25°: 4mm

Solubility in water: 34parts per billion

Evaporation rate (butyl acetate = 1): 0.7

Viscosity: 1-2cSt.

FIRE & EXPLOSION DATA

Flash Point, COC: 39°C (102°F)

Flammability Limits- LEL: 0.9%

Autoignition Temp: 418°C (784°F)

UEL: 13.8%

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.

Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame. Liquid generates strong static charge when poured.

ENVIRONMENTAL INFORMATION

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal.

Recommended Disposal: May be incinerated. Alternately, absorb onto clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: Vapors may cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation of vapors or particulates will irritate the respiratory tract. Overexposure may produce coughing, headache and nausea.

Oral Toxicity- rat, LD50: >5000mg/kg

Chronic Toxicity: There are no known chronic effects related to this compound.

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

REACTIVITY DATA

Stability: Stable in sealed containers in a cool place.

Conditions to avoid: Combustible; avoid contact with heat, sparks or open flame.

Incompatibility (materials to avoid): Avoid contact with peroxides, oxidizing agents.

Hazardous decomposition products: Organic Acid Vapors.

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor amine gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed containers.

Containers require grounding during use.

TRANSPORTATION

DOT SHIPPING NAME: FLAMMABLE LIQUID, N.O.S. (POLYDIMETHYLSILOXANE)

DOT HAZARD CLASS: 3

DOT LABELS: Flammable Liquid

DOT ID No: UN1993

PG: III

Prepared by safety and environmental affairs ISSUE DATE PSF-1cSt: 6/14/04

SUPERSEDES: NONE

The information contained in this document has been gathered from reference materials and/or Clearco Products test data and is to the best knowledge and belief of Clearco Products, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones that exist. Clearco Products makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.