



CLEARCO THREAD LUBRICANT



Dipping: Dip the entire cone into the Silicone Thread Lubricant. It takes about 20-seconds to penetrate a one lb. cone of cotton thread. Synthetic threads may require a second application.

Clearco Thread Lubricant is a **STAINLESS – ODORLESS lubricant for the Thread Industry**. The Thread Lubricant deposits a stainless coating on the thread that cools the needle and prevents thread breakage. Other benefits include easier needle penetration & elimination of carbon, sizing or adhesive buildups on the needle or hook.

FEATURES

- | | |
|---|---|
| <ul style="list-style-type: none"> • Prevents Thread Breakage • Cools Needle • Prevents Fusing of needle to material | <ul style="list-style-type: none"> • Provides Protective Finish for Thread • Reduces Friction • Reduces Heat Buildup |
|---|---|



Reduces Friction on the needle



Provides a protective finish



Prevents breakage

PROPERTIES

Form	Liquid
Appearance	Clear
Color Stability	Excellent
Resistance to Degradation	Excellent
Solubility	Dissolves in many Solvents It is Not Water Soluble
Availability	5-gallon cube containers with Spigot. 55 gallon drums
Flammability	HMIS Rating 2

CAS Information

Petroleum Solvent.....	CAS-6472-48-9
Petroleum Mineral Oil.....	CAS-8042-47-5
Paraffin Wax.	CAS-64742-43-4
Stearate, Methyl.....	CAS112-61-8

For More Information or To Request a Sample, Contact:

Clearco Products Co., Inc.
 3430 G. Progress Drive
 Bensalem, PA 19020
 Tel: 215 639-2640
 Fax: 215 639-2919
 Email: info@clearcoproducts.com
 Web: www.clearcoproducts.com

HOW TO APPLY

Dipping: Dip the entire cone into the Silicone Thread Lubricant. It takes about 20-seconds to penetrate a one lb. cone of cotton thread. Synthetic threads may require a second application.

Other: Spray entire surface of thread...top and sides. This will penetrate slightly and require several periodic applications. When available, felts can be saturated with lubricant. Thread is treated as it passes between felts.

PERFORMANCE

Clearco Thread Lubricant is specially formulated. It will, ultimately, **Speed Production & Eliminate Downtime.**

ENVIRONMENTAL

Thread Lubricant contains no CFC's or any other Ozone Depleting **Chemicals. It is Odorless, Non-Staining & Greaseless**

ECONOMICAL

Available in 5-Gallon Cubes & 55-Gallon Drums.

CLEARCO

3430 G PROGRESS DRIVE
BENSALEM, PA 19020

Tel: (800) 533-5823

Fax: (215) 639-2919

Email: info@clearcoproducts.com

Web Address: www.clearcoproducts.com