

Product Information

Mr. Clearco Food Grade Silicone Spray NSF H1

NSF H1 Registered Food Grade Silicone Lubricant...meets FDA 21 CFR specifications for incidental food contact



13 oz. net wt. (20 oz. can size)

Mr. Clearco Food Grade Silicone Spray is formulated for use in Food Packing and Food Processing areas to prevent sticking & allow materials to slide easier. It prevents food buildups and cuts clean-up times to a fraction.

Mr. Clearco Food Grade Silicone Spray is registered with the NSF / USDA Nonfood Compounds Registration Program as an NSF H1 lubricant where incidental contact with food may occur in food processing areas. It meets corresponding FDA 21 CFR regulatory requirements as well.

Mr. Clearco Food Grade Silicone Spray is acceptable as a lubricant with Incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank enclosures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food.

How to Use: Spray a fine mist on the area to be treated. A fine spray is all that is required to keep materials moving on bins, chutes, walls & surfaces. It prevents sticking on buildups of sugar and food, allowing for fast cleanup at the end of the day or the shift.



Allows plastic wrapped products to slide



Prevents sugar-buildups



Allow products to move on conveyors without sticking

Packing

Can size	20 oz. can
Net wt. per can	13 oz. net wt
Case Packing	12x13 oz. net wt. cans
Weight	14 lbs. per case

Food Processing Applications Include:

- Eliminates sugar build-ups and breakdowns when applied to filler tubes, Chrome plates and spray pumps
- Prevents food from sticking to conveyors, ovens, freezing trays, baking tins, knives, cooking coils, evaporators & other processing equipment
- lubricant/release agent in the manufacture of such food-packaging materials such as paper and paperboard
- Prevents sticking on chutes, bins, walls and surfaces. Keeps material moving and prevents adhesion of greases and oils.
- Lubricates surface of wood, metal, plastic, vinyl, rubber, leather etc.- eliminates squeaking
- Prevents jamming of equipment caused by glues, adhesives, waxes etc.
- Allows cellophane, pilofilm, saran and vinyl polyethylene to move freely over sprayed surfaces.
- Provides anti-friction protection on Knives & Blades, preventing fusing of plastics & synthetics.

NSF & FDA 21 CFR Information

NSF H1 Registration No: Registration # 05281

Meets corresponding FDA 21 CFR specifications, including FDA 21 CFR 178.3570 Lubricant with Incidental Food Contact.

CAS Information

Liquefied Petroleum Gas	CAS-68476-85-7
Dimethylpolysiloxane	CAS-63148-62-9

Warning: Do NOT use on Hot surfaces or in the presence of an ignition source!! Product contains highly flammable solvent and propellant

Packaging/ minimum order

1-case (12 x 13oz net wt. cans per case F.O.B. Phila, PA U.S.A.

For Information, Contact:

CLEARCO PRODUCTS CO., INC.

3430 G Progress Drive Bensalem, PA 19020 U.S.A.

Tel: 215 639-2640 Fax: 215 639-2919

Email: info@clearcoproducts.com
Web: www.clearcoproducts.com