



## PSF-5,000cSt Silicone Damping Fluid

High Viscosity Polydimethylsiloxane Fluid (CAS # 63148-62-9)...meets VV-D-1078 Silicone as Damping Fluid



*PSF-5,000cSt Silicone Damping Fluid is a high viscosity polydimethylsiloxane that meets federal spec VV-D-1078 "Silicone as Damping Fluid".*

**PSF-5,000cSt Silicone Damping Fluid** is a high viscosity linear Polydimethylsiloxane (CAS#63148-62-9) fluids with a viscosity of 5,000cSt (centistokes) @ 25°C.

**PSF-5,000cSt Silicone Damping Fluid** is a hydrophobic fluid that is characterized by its wide service temperature range, high oxidation resistance, high viscosity, high dielectric strength, high resistance to shear, low pour points, low V.T.C. (little viscosity change even at extremely low temperature), excellent lubrication & high damping action.

**PSF-5,000cSt Silicone Damping Fluid** meets Federal Spec **VV-D-1078 "Silicone as Damping Fluid**. It is used in a wide range of military and industrial liquid filled gauges, level controllers, rotary dampers, temperature and process recorders, control valves, calibration equipment, flow meters, thermostats, dashpots, monitoring systems avionic gauges and aviation instruments to dampen vibration, dampen pulsation, and dampen torque.

**PSF-5,000cSt Silicone Damping Fluid** is particularly effective for use in instruments and gauges that will operate at a wide service temperature range. The fluid is hydrophobic and prevents humidity from entering the gauge/instrument housing. This is very important. At low temperatures, water condensation can freeze and cause damage to the sensitive parts within the gauge/instrument housing. Ultimately, **Silicone Damping Fluids** will extend the service life of the equipment that it fills and provide more accurate readings even in the harshest of conditions.

### Specifications

Product code	PSF-5,000cSt
Chemical Name	Polydimethylsiloxane
CAS #	63148-62-9
Appearance	Clear, colorless odorless fluid
Meets NSN No.	NSN 9150-00-664-3829
Consistency	Honey

### Properties

Appearance	Clear
Specific Gravity	0.975
Refractive Index	1.4035
Flash Point (Open Cup)	315°C
Pour Point	-50°C
V.T.C.	0.61
Surface Tension @ 25°C	21.3
Thermal Conductivity g/cal/cm/sec °C	0.00038
Thermal Expansion cc/cc °C	0.00096
Dielectric Constant 50Hz	2.75
Dielectric Strength (volts/mil)	400

### Features

- Dampen vibration in gauges, instruments, meters and avionic instruments
- Protects internal components against vibration, freezing and corrosion.
- Extends service life of gauges, instruments, meters and avionic instruments.
- Wide Service Temperature Range
- High Oxidation resistance
- Low viscosity change at temperature (low V.T.C.)
- Inert to virtually all o-rings, gaskets, seals and valves \*
- Meets NSN 9150-00-664-3829
- High Dielectric Strength

\* not recommended for Silicone o-rings due to possibility of swelling

### Packaging

1-gallon.....3.6kg net wt.

5-gallon pail.....18kg net wt.

55-gallon drum.....200kg net wt.

F.O.B. Phila, PA U.S.A.

### Environmental & VOC Status

*Clearco Pure Silicone Fluid is exempt from Federal VOC Regulations, including California (CARB) and OTC Regulations. It does not contribute to ozone depletion and global warming. In addition, it meets the following:*

- RoHS Compliant
- HAP-free
- VOC Exempt

### For More Info, Contact:

#### Clearco Products Co., Inc.

15 York Road  
Willow Grove, PA 19090  
U.S.A.

Tel: (215) 366-7860

Fax: (215) 366-7862

Email: [info@clearcoproducts.com](mailto:info@clearcoproducts.com)

Web: [www.clearcoproducts.com](http://www.clearcoproducts.com)