



## Product Information

# PSF-5,000cSt Pure Silicone Fluid

High Viscosity Polydimethylsiloxane Fluid / PDMS Silicone Fluid (CAS # 63148-62-9)



PSF-5K Pure Silicone Fluid is a high viscosity PDMS silicone oil (CAS# 63148-62-9)

**PSF-5,000cSt Pure Silicone Fluid** is a clear, colorless and odorless 100% linear Polydimethylsiloxane fluid / PDMS Silicone Fluid (CAS # 63148-62-9 with a viscosity of 5,000cSt (centistokes) @ 25°C.

PSF-5,000cSt Pure Silicone Fluid is characterized by its high viscosity, hydrophobic nature, high damping action, low V.T.C. (little viscosity change at both high and low temperatures), wide service temperature range, high resistance to oxidation, excellent lubricity, high dielectric strength and inertness.

PSF-5,000cSt Silicone Fluid is widely used as a damping fluid in a range of military, industrial and avionic gauges, meters, instruments, and monitoring systems.

In addition, Pure Silicone Fluid 5,000cSt is inert to virtually all plastic, rubber and metal surfaces. It is widely used as a lubricant for O-rings, gaskets, valves and seals.

Uses include High Damping Action Fluid, High Viscosity Dielectric Fluid, Lubricant for Rubber and plastics, O-Ring Lubricant, Valve and Gasket lubricant.

### Specifications

Product code	PSF-5,000cSt
Chemical Name	Polydimethylsiloxane / PDMS Silicone
INCI Name	Dimethicone
CAS #	63148-62-9
Appearance	Clear, colorless odorless fluid

### Properties

Appearance	Clear
Specific Gravity	0.975
Refractive Index	1.4035
Flash Point (Open Cup) °C (°F)	315°C
Pour Point °C (°F)	-50°C
V.T.C.	0.61
Surface Tension @ 25°C	21.3
Thermal Conductivity g/cal/cm/sec °C	0.00038
Thermal Expansion cc/cc °C	0.00096
Dielectric Constant 50Hz	2.75
Dielectric Strength (volts/mil)	400

### Features

- High Viscosity PDMS Silicone Oil
- Excellent Lubrication
- Wide Service Temperature Range
- High Resistance to Oxidation
- High Damping Action
- High Dielectric Strength
- High resistance to shear
- Hydrophobic
- Chemically Inert
- Excellent Thermal Stability

### Packaging

1-gallon (3.785L).....	3.6kg net wt.
5-gallon pail (18.9L).....	18kg net wt.
55-gallon drum.....	190kg net wt.

F.O.B. Phila., PA U.S.A.

### Environmental & VOC Status

Clearco Pure Silicone Fluid is exempt from Federal VOC Regulations, including California (CARB) and OTC Regulations. It does not contribute to ozone depletion and global warming. In addition, it meets the following:

- RoHS Compliant
- HAP-free
- VOC Exempt

### For More Info, Contact:

#### Clearco Products Co., Inc.

15 York Road  
Willow Grove, PA 19090  
U.S.A.

Tel: (215) 366-7860

Fax: (215) 366-7862

Email: [info@clearcoproducts.com](mailto:info@clearcoproducts.com)

Web: [www.clearcoproducts.com](http://www.clearcoproducts.com)