



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/18/2025

Reviewed on 07/18/2025

1 Identification

- **Product Identifier**
- **Trade name:** Clearslip #2 Silicone Lubricant
- **Product Number:** CS#2
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description** Silicone Fluid, Polydimethylsiloxane dispersed in isoparffinic solvent.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Clearco Products
15 York Rd
Willow Grove, PA 19090
Ph: 1-215-366-7860
Fx: 1-215-366-7862
- **Emergency telephone number: Contract# # MIS0001670**
VelocityEHS: 1-255-3924 (Domestic)
+01-813-248-0585 (International)

* 2 Hazard(s) Identification

- **Classification of the substance or mixture:**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements:**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS02 GHS08

- **Signal word:** Danger

- **Hazard-determining components of labeling:**

Petroleum Solvents - Naphtha (petroleum)

- **Hazard statements:**

Flammable liquid and vapor.

Causes eye irritation.

May be fatal if swallowed and enters airways.

- **Precautionary statements:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/25/2015

Reviewed on 11/23/2015

Trade name: Clearslip #2 Silicone Lubricant

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If eye irritation persists: Get medical advice/attention.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**

15 % of the mixture consists of component(s) of unknown toxicity.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 2

Reactivity = 0

· **HMS-ratings (scale 0 - 4)**



Health = *1

Fire = 2

Reactivity = 0

· **Hazard(s) not otherwise classified (HNOC):** None known

* 3 Composition/Information on Ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

CAS: 64742-48-9	Petroleum Solvents - Naphtha (petroleum) ⚠ Asp. Tox. 1, H304; Flam. Liq. 4, H227	85-95%
RTECS: JT6485000	Polydimethylsiloxane Eye Irrit. 2B, H320	5-15%

4 First-Aid Measures

· **Description of first aid measures:**

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· **After eye contact:**

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If swallowed and symptoms occur, consult a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

(Contd. on page 3)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/25/2015

Reviewed on 11/23/2015

Trade name: Clearslip #2 Silicone Lubricant

- **Indication of any immediate medical attention and special treatment needed:**
No further relevant information available.

5 Fire-Fighting Measures

- **Extinguishing media:**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture:**
Combustible liquid. Vapors can travel to a source of ignition and flash back.
Explosive mixtures may occur at temperatures at or above flashpoint.
- **Advice for firefighters:**
- **Protective equipment:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Protect from heat.
- **Conditions for safe storage, including any incompatibilities:**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in the original container.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
No further relevant information available..
Protect from heat and direct sunlight.
- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with occupational exposure limits:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/25/2015

Reviewed on 11/23/2015

Trade name: Clearslip #2 Silicone Lubricant

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 The usual precautionary measures for handling chemicals should be followed.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing and wash before reuse.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

- **Material of gloves:**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material:**
 The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.
- **Eye protection:**



Tightly sealed goggles

* **9 Physical and Chemical Properties**

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	Colorless
- **Odor:** Characteristic
- **Odor threshold:** Not determined.
- **pH-value:** Acidic
- **Change in condition**

Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	177 °C (351 °F)
- **Flash point:** 55 °C (131 °F) (Closed Cup)
- **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 5)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/25/2015

Reviewed on 11/23/2015

Trade name: Clearslip #2 Silicone Lubricant

- **Ignition temperature:**
 - **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Not determined.
- **Explosion limits:**
 - **Lower:** 0.6 Vol %
 - **Upper:** 7.0 Vol %
- **Vapor pressure @ 20 °C (68 °F):** 1 hPa (1 mm Hg)
- **Density @ 20 °C (68 °F):** 0.811 g/cm³ (6.768 lbs/gal)
- **Relative density:** Not determined.
- **Vapor density:** Not determined.
- **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with:**
 - **Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - **Dynamic:** Not determined.
 - **Kinematic:** Not determined.
- **Solvent content:**
 - **Organic solvents:** 0.0 %
 - **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)

- **Primary irritant effect:**

- **On the skin:** Irritant to skin and mucous membranes.

- **On the eye:**

- Irritating effect.

- Causes serious eye irritation.

(Contd. on page 6)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/25/2015

Reviewed on 11/23/2015

Trade name: Clearslip #2 Silicone Lubricant

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic categories:

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

12 Ecological Information

Toxicity:

Aquatic toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No further relevant information available.

13 Disposal Considerations

Waste treatment methods:

Recommendation: Recycle or dispose with household trash.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

*14 Transport Information

UN-Number:

DOT

NA1993

ADR, IMDG, IATA

UN1993

UN proper shipping name:

DOT

COMBUSTIBLE LIQUID, N.O.S (Petroleum Solvents - Naphtha (petroleum))

ADR

UN1993 Flammable liquids, n.o.s. (Petroleum Solvents - Naphtha (petroleum))

IMDG

FLAMMABLE LIQUID, N.O.S. (Petroleum Solvents - Naphtha (petroleum))

IATA

Flammable liquid, n.o.s. (Petroleum Solvents - Naphtha (petroleum))

(Contd. on page 7)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/25/2015

Reviewed on 11/23/2015

Trade name: Clearslip #2 Silicone Lubricant**· Transport hazard class(es):****· DOT**

· Class: 3 Combustible liquids
· Label: 3

· ADR

· Class: 3 (F1) Flammable liquids
· Label: 3

· IMDG, IATA

· Class: 3 Flammable liquids
· Label: 3
· Packing group: III
· DOT, ADR, IMDG, IATA III
· Environmental hazards: Not applicable.
· Special precautions for user: Warning: Flammable liquids
· Danger code (Kemler): 30
· EMS Number: F-E,S-E
· Stowage Category: A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable.

· Transport/Additional information:**· DOT**

· Quantity limitations: On passenger aircraft/rail: 60 L
 On cargo aircraft only: 220 L
· Remarks: Not regulated if less than 119 gallons

· ADR

· Excepted quantities (EQ): Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ): 5L
· Excepted quantities (EQ): Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 8)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/25/2015

Reviewed on 11/23/2015

Trade name: Clearslip #2 Silicone Lubricant

- **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUIDS, N.O.S. (PETROLEUM SOLVENTS - NAPHTHA (PETROLEUM)), 3, III

*15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· Section 355 (extremely hazardous substances):
None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):
None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):
All ingredients are listed.

· **California Proposition 65:**

· Chemicals known to cause cancer:
None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:
None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:
None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:
None of the ingredients are listed.

· **Carcinogenic categories:**

· EPA (Environmental Protection Agency):
None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):
None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):
None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS02 GHS08

· **Signal word:** Danger

· **Hazard-determining components of labeling:**

Petroleum Solvents - Naphtha (petroleum)

· **Hazard statements:**

Flammable liquid and vapor.

Causes eye irritation.

May be fatal if swallowed and enters airways.

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/25/2015

Reviewed on 11/23/2015

Trade name: Clearslip #2 Silicone Lubricant**Precautionary statements:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Wear protective gloves / eye protection / face protection.
 Ground/bond container and receiving equipment.
 Keep container tightly closed.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Wash thoroughly after handling.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 If eye irritation persists: Get medical advice/attention.
 Do NOT induce vomiting.
 In case of fire: Use for extinction: CO2, powder or water spray.
 Store locked up.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

State Right to Know:

CAS: 64742-48-9	Petroleum Solvents - Naphtha (petroleum)  Asp. Tox. 1, H304; Flam. Liq. 4, H227	85-95%
RTECS: JT6485000	Polydimethylsiloxane Eye Irrit. 2B, H320	5-15%

All ingredients are listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

Date of preparation / last revision: 11/25/2015 / 4

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health

(Contd. on page 10)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/25/2015

Reviewed on 11/23/2015

Trade name: Clearslip #2 Silicone Lubricant

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Asp. Tox. 1: Aspiration hazard, Hazard Category 1